


GBU SILICON BRIDGE RECTIFIERV

FEATURES

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Construction utilizes void-free molded plastic technique
- High reliability
- High temperature soldering guaranteed: 260 °C/10 seconds at terminals
- Component in accordance to RoHS 2015/863 and WEEE 2012/19/EU

MECHANICAL DATA

- Case style: GUB molded plastic
- Mounting position: Any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		GBU 25A	GBU 25B	GBU 25D	GBU 25G	GBU 25J	GBU 25K	GBU 25M	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward $T_c=100^{\circ}C$ output current	$I_{F(AV)}$	25.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}	340							A
Maximum instantaneous forward voltage at 12.5 A	V_F	1.0							V
Maximum reverse current @ $T_A=25^{\circ}C$ at rated DC blocking voltage @ $T_A=125^{\circ}C$	I_R	5.0 500.0							μA mA
Typical junction capacitance per leg	C_J	211				94			pF
Typical thermal resistance per leg	$R_{\theta JA}$	21.0							$^{\circ}C/W$
	$R_{\theta JC}$	2.2							
Operating junction temperature range	T_J	- 55 ---- + 150							$^{\circ}C$
Storage temperature range	T_{STG}	- 55 ---- + 150							$^{\circ}C$

RATINGS AND CHARACTERISTIC CURVES

FIG.1 – DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 – TYPICAL FORWARD CHARACTERISTIC




FIG.3 – MAXIMUM NON-REPETITIVE PEAK FORWARD DURGE CURRENT




FIG.4 – TYPICAL REVERSE CHARACTERISTIC




FIG.5 – TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.6 – TYPICAL TRANSIENT THERMAL IMPEDANCE

