


KBJ SILICON BRIDGE RECTIFIERV

FEATURES

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Construction utilizes void-free molded plastic technique
- High reliability
- High temperature soldering guaranteed: 260 °C/10 seconds at terminals
- Component in accordance to RoHs 2015/863 and WEEE 2012/19/EU

MECHANICAL DATA

- Case style: KBJ molded plastic
- Mounting position: Any



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		KBJ 6A	KBJ 6B	KBJ 6D	KBJ 6G	KBJ 6J	KBJ 6K	KBJ 6M	UNITS
Maximum recurrent peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum average forward output current @T _A =110°C	I _{F(AV)}				6.0				A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I _{FSM}				150.0				A
Maximum instantaneous forward voltage at 3.0 A	V _F				1.0				V
Maximum reverse current @T _A =25°C at rated DC blocking voltage @T _A =100°C	I _R				10.0				µA
					1.0				mA
Typical junction capacitance per element	C _J				55				pF
Typical thermal resistance	R _{θJC}				1.8				°C/W
Operating junction temperature range	T _J				- 55 ---- + 150				°C
Storage temperature range	T _{STG}				- 55 ---- + 150				°C

RATINGS AND CHARACTERISTIC CURVES

FIG.1 – PEAK FORWARD SURGE CURRENT




FIG.2 – FORWARD DERATING CURVE




FIG.3 -- TYPICAL FORWARD CHARACTERISTIC




FIG.4 -- TYPICAL JUNCTION CAPACITANCE

